



R-22
SPLIT TYPE
AIR CONDITIONER



FEATURES:



Auto Swing

Distributes cool air to a maximum area by moving horizontal flaps automatically



Turbo Operation

With this function, room temperature is cooled down in shortest time.



Cleanable Panel

Front panel of the indoor unit is easy to be cleaned for periodic maintenance.



Self-Diagnosis Function

Error protection code is displayed on the indoor unit if some abnormality with the unit.



Louver Memory Function

The louver is automatically angled to the same position when you re-start the unit.



LCD Display

Control panel of the indoor unit adopts LCD. It shows temperature display.



Auto Re-start

The unit will automatically start when power is restored if the unit was running when there is power interruption.



Sleep Mode

Enables the unit to automatically increase setting temp. 1°C for the first 2 hours to save energy.

SPECIFICATIONS:

Model		Indoor	WIHXF3-09KW2D	WIHXF3-12KW2D	WIHXF3-18KW2D	WIHXF3-24KW2D	WIHXF3-30KW2D
		Outdoor	WCHXF3-09K2D	WCHXF3-12K2D	WCHXF3-18K2D	WCHXF3-24K2D	WCHXF3-30K2D
Power Supply		Ph-V-Hz	220-230V~ 60Hz, 1Ph				
Cooling	Capacity	Btu/h	9000	12000	18000	24000	30000
	Input	W	960	1240	1800	2380	2700
	Rated Current	A	4.4	5.5	8.5	12.0	13.0
	EER	W/W	2.60	2.60	2.61	2.59	2.61
Indoor Unit	Indoor Air Flow (Hi/Med/Lo)	m3/h	450/370/300	550/470/350	700/620/450	1050/950/750	1050/950/750
	Moisture Removal	L/h	1.0	1.1	1.6	2.2	2.6
	Noise Level (Hi/Med/Lo)	dB(A)	40//29	41/38/32	42/39/33	47/44/39	46/43/38
	Unit Dimension (W x D x H)	mm	680 x 255 x 178	770 x 255 x 188	905 x 275 x 198	1030 x 315 x 218	1030 x 315 x 218
	Packing Dimension (W x D x H)	mm	745 x 255 x 330	835 x 265 x 330	970 x 270 x 345	1115 x 395 x 300	1115 x 395 x 300
	Net Weight	Kg	7	7.5	9	12	12
	Gross Weight	Kg	8	9	11	15	15
Outdoor Unit	Noise Level	dB(A)	54	54	56	58	57
	Unit Dimension (W x D x H)	mm	685 x 260 x 430	700 x 240 x 540	780 x 250 x 540	820 x 330 x 595	845 x 320 x 700
	Packing Dimension (W x D x H)	mm	795 x 345 x 495	815 x 325 x 580	910 x 335 x 585	940 x 415 x 645	965 x 395 x 755
	Net Weight	Kg	21	24.5	29.5	37.5	45.5
	Gross Weight	Kg	23	26.5	33	40.5	49
Refrigerant Type		g	R22/370g	R22/450g	R22/700g	R22/950g	R22/1050g
Design Pressure		MPa	2.6/1.0	2.6/1.0	2.6/1.0	2.6/1.0	2.6/1.0
Refrigerant Piping	Liquid Side	mm(inch)	Φ6.35 (1/4")	Φ6.35 (1/4")	Φ6.35 (1/4")	Φ9.52 (3/8")	Φ9.52 (3/8")
	Gas Side	mm(inch)	Φ9.52 (3/8")	Φ12.7 (1/2")	Φ12.7 (1/2")	Φ16 (5/8")	Φ16 (5/8")

Specifications and illustrations subject to change without notice and without incurring obligations.

For More Information, call or visit your Westinghouse Dealer



NORDYNE International
11500 N.W. 34th Street
Miami, Florida, U.S.A. 33178

Phone: 1 (305) 593-9061
e-mail: sales@westinghousevac-intl.com
www.westinghousevac-intl.com